

Mobilogix MT2600

TRACK. MONITOR. MANAGE. OPTIMIZE.



The MT2600 is a powered tracking solution with multiple I/O and embedded GPS providing remote access and monitoring capabilities in a robust industrial design.

Pair the MT2600 with our Fusion IoT platform and enable a fully integrated end to end solution for track, trace and recovery of assets as well as low power Bluetooth beacon sensor data aggregation.

The MT2600 can also serve as a gateway for multiple Bluetooth beacons or tags, providing a low-cost solution when managing multiple assets at scale is critical.



THE MT2600 IS AVAILABLE TO BE WHITE LABELED AND CUSTOM BRANDED.

SMALL AND POWERFUL

The MT2600 enables track and trace workflows with installs as simple as 2 wires. With an on-board antenna and IMU, the MT2600 is ready to go out of the box for powered asset traceability.

CONFIGURABLE & REAL TIME

As an always on tracker with multiple power source options, the MT2600 of devices can provide highly granular tracking with configurable location reporting intervals.

GROWS WITH YOUR NEEDS

Add one or more BTM250 beacons to your solution to monitor multiple assets or zones while the MT2600 acts as a gateway. With gateway mode enabled, all data recorded at each BTM250 will be available in reports with the Fusion IoT cloud platform via the MT2600 cellular backhaul.

VERSATILE

With multiple I/O configurations the MT2600 can meet various needs including: Ignition relay, starter disable, temperature probes, door monitor, emergency button and other general I/O needs.

Mobilogix MT2600

TRACK. MONITOR. MANAGE. OPTIMIZE.



Key Features:

- Real-Time Tracking
- Real Time Notifications
- Small Form Factor
- Quick and Easy Installation
- Motion Detection
- Starter Disable
- Tamper Alarm
- Speed Alarm
- OTA (Over-the-Air) Updates
- Reporting Interval Selection
- Trip Reporting
- Geofence entry/exit Alarm
- Low-Battery Alarm
- Unauthorized Movement Alarm
- Four Tracking Modes
- Bluetooth Beacon Gateway

Fusion IoT Integration

- Secure Web Login
- Native Android and iOS Apps
- Manage MT2600 Everywhere
- Fusion IoT White Label Option
- Peripheral Asset Tagging and Tracking
- Inventory Management
- Device Status Provisioning

Technical Specifications

	MT2600
Modem	Quectel® MC60
Antenna	Internal
Cellular Service	2G GPRS, Quad Band
GNSS	GPS, Glonass
Sensors	Full IMU
Bluetooth	Bluetooth 5.1
Power Input	8-24 VDC
Backup Battery	3.7 V Li-ion (rechargeable)
Enclosure	98 x 51 x 20mm, IP67
I/O	3 Input, 3 Output
Operating Temperature	-40°C to +85°C
Regulatory	FCC/IC
Safety	RoHS 2
Warranty	1 year



5500 Trabuco Rd, Suite 150, Irvine, CA 92620
Tel: +1.949.748.8895

MOBILOGIX.com

Mobilogix, the logo and the M design are trademarks of Mobilogix, Inc.
Other registered trademarks that appear on this brochure are the property of the respective owners